

Ledline[™]

24V IP67 High Efficiency Single Colour LED Strip







AA-ST12110IP-30	11W	160	3000K	1320lm	120		
AA-ST12110IP-40	11W	160	4000K	1430lm	130		
AA-ST12110IP-50	11W	160	5000K	1469lm	135		
AA-ST12110IP-65	11W	160	6500K	1508lm	137		
Accessories							
AA-STA12IP	LEDline™ IP67 strip connector kit						
	Description				Metres per driver		
Cat. No.	Description			Metres	per driver		
Cat. No. LED Drivers	Description			Metres	per driver		
04.1.10.	·	nable IP67 24V cc	nstant voltage dri		per driver 3m		
LED Drivers	35W non-dimr	nable IP67 24V co	· ·	iver	•		
LED Drivers SV-LPV-35-24	35W non-dimr		nstant voltage dri	iver iver	3m		
LED Drivers SV-LPV-35-24 SV-LPV-60-24	35W non-dimr 60W non-dimr 100W non-dim	mable IP67 24V co	nstant voltage dri constant voltage d	iver iver Iriver	3m 5m		

Product Features:

Max single run 5m

- Single colour flexible strip with 3M[™] self adhesive backing
- High efficiency up to 137lm/W
- Cut points every 50mm for maximum flexibility
- Beam angle of 120°
- 160 LEDs per metre
- For runs over 5m individual lengths should be connected in parallel
- Reel length of 30m

Line Drawing



Connectors



AA-STA12IP

IP Rated kit includes:

- 2 power leads
- 2 end caps
- 4 starter sleeves
- 1 tube of sealant
- 6 fixing clips
- 12 fixing screws Requires soldering

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the repalcement of this product and Aurora reserve the right to alter.