




Colour options:



Sku	Watts	lm/W	Lumens	Colour	Beam
<b>Non-Dimmable</b>					
AA-BDL367-30*	7W	84	590lm	3000K	90°
AA-BDL367-40*	7W	91	640lm	4000K	90°
AA-BDL4410-30*	10W	82	820lm	3000K	90°
AA-BDL4410-40*	10W	90	900lm	4000K	90°
AA-BDL5714-30*	14W	86	1200lm	3000K	90°
AA-BDL5714-40*	14W	93	1300lm	4000K	90°
AA-BDL6817-30*	17W	88	1500lm	3000K	90°
AA-BDL6817-40*	17W	94	1600lm	4000K	90°
AA-BDL9625-30*	25W	89	2230lm	3000K	90°
AA-BDL9625-40*	25W	94	2350lm	4000K	90°
<b>Dimmable</b>					
AA-BDDL367-30*	7W	77	540lm	3000K	90°
AA-BDDL367-40*	7W	84	590lm	4000K	90°
AA-BDDL4410-30*	10W	70	700lm	3000K	90°
AA-BDDL4410-40*	10W	75	750lm	4000K	90°
AA-BDDL5714-30*	14W	86	1200lm	3000K	90°
AA-BDDL5714-40*	14W	93	1300lm	4000K	90°
AA-BDDL6817-30*	17W	88	1500lm	3000K	90°
AA-BDDL6817-40*	17W	94	1600lm	4000K	90°
AA-BDDL9625-30*	25W	89	2230lm	3000K	90°
AA-BDDL9625-40*	25W	94	2350lm	4000K	90°

\*Add suffix **W** or **BLK** for White or Black finish

## Line Drawing



### AA-BDL/BDDL367

(H) 64mm Height  
(OD) 92mm Overall (Ø)  
(CO) 68-80mm Cutout (Ø)

### AA-BDL/BDDL5714

(H) 75mm Height  
(OD) 145mm Overall (Ø)  
(CO) 120-130mm Cutout (Ø)

### AA-BDL/BDDL9625

(H) 95mm Height  
(OD) 244mm Overall (Ø)  
(CO) 195-210mm Cutout (Ø)

### AA-BDL/BDDL4410

(H) 73mm Height  
(OD) 113mm Overall (Ø)  
(CO) 90-102mm Cutout (Ø)


### AA-BDL/BDDL6817

(H) 79mm Height  
(OD) 174mm Overall (Ø)


(CO) 145-155mm Cutout (Ø)

## Polar Curves

### 17W 4000K 90° Beam



### 25W 4000K 90° Beam



## Product Features:

- ThermoTec<sup>™</sup> heat management technology
- Delivering up to 94lm/W
- 90° beam angle
- Pre-wired with plug and play DC male and female connectors
- Opal diffuser to reduce glare and for even light distribution
- Supplied with integrated LED driver
- Designed for a variety of applications
- Ideal for retrofit with a wide range of cutouts available
- Polycarbonate construction

## Product Specification:

Installation Type	Recessed
Input Voltage	220 - 240V
Luminaire Materials	Plastic Coated, Aluminium Housing
Lifetime	50000
CRI	80
IK Rating	IK06
IP Rating	IP20
Warranty	3 Years

## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.