



**HIGH  
EFFICIENCY**

Sku	Watts	lm/W	Lumens	Colour	Beam
<b>Single</b>					
<b>EN-BA1222*-40</b>	20W	140	2800lm	4000K	120°
<b>Twin</b>					
<b>EN-BA1243*-40</b>	38W	140	5300lm	4000K	120°


\*Add suffix **EM**, **MS** for **Emergency** or **Microwave Sensor** options.

Colour :



White


## Line Drawing



<b>EN-BA1222</b>	<b>EN-BA1243</b>
(L) 1170mm Length	(L) 1170mm Length
(W) 61mm Width	(W) 61mm Width
(H) 71mm Height	(H) 71mm Height

## Polar Curves

**20W 4000K 120°**



## Product Features:

- Updated design with a push clip release mechanism at each end
- Delivering up to 140lm/W
- Hinged gear tray for fast installation
- Push-fit terminals
- Knockouts for cable entry on both ends
- Multiple BESA mounting points (matches traditional fluorescent)
- IK08 rated
- Adjustable light detector from 2-50 lux for microwave option
- Adjustable hold time of 5 seconds to 30 minutes for microwave option
- Opal polycarbonate diffuser for even light distribution
- Can be surface mounted or suspended

## Product Specification:

Installation Type	Surface & Suspended
Input Voltage	220 - 240V
Luminaire Materials	Die Cast Aluminium, Pressed Steel
Lifetime	50000
CRI	80
IK Rating	IK08
IP Rating	IP20
Warranty	5 Years

## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.