





SKU	Base	Watts	lm/W	Lumens	Colour	Beam
Non-Dimmable						
AU-EMGU05-30	GU10	5W	80	400lm	3000K	60°
AU-EMGU05-40	GU10	5W	80	400lm	4000K	60°

Line Drawing



AU-EMGU05
(OD) 60mm Overall (Ø)
(L) 125mm Length

Polar Curves



Product Features:

- Provides automatic illumination during a power outage
- Delivering 80lm/W
- 3 hour emergency backup
- 400 lumen during normal operation
- Lumens during 1st hour of emergency operation > 70lm
- Lumens during 2nd hour of emergency operation > 40lm
- Lumens during 3rd hour+ of emergency operation > 35lm
- Deep body for longer battery life
- 60° beam angle
- 6500K when operating in emergency mode
- Can be switched on/off during emergency mode

Product Specification:

Input Voltage	220 - 240V
Luminaire Materials	Polycarbonate
Lifetime L70	25000
CRI	80
IK Rating	IK06
IP Rating	IP40
Warranty	2 Years

Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.