



Colour :



White


SKU	Watts	lm/W	Lumens	Colour	Beam
-----	-------	------	--------	--------	------

Twin

EN-ANTL1238*-40	38W	116	4400lm	4000K	120°
EN-ANTL1555*-40	55W	120	6600lm	4000K	120°

*Add suffix **EM** for **Emergency** option available upon request


Line Drawing



EN-ANTL1238	EN-ANTL1555
(L) 1227mm Length	(L) 1510mm Length
(W) 67mm Width	(W) 67mm Width
(H) 70mm Height	(H) 70mm Height

Polar Curves

55W 4000K 120°



Product Features:

- Vandal resistant high impact polycarbonate housing
- Delivering up to 120lm/W
- Opal diffuser to provide smooth even light distribution
- Adjustable push fit terminals at either end for quicker installation and through wiring
- 2 x IP66 rated cable glands supplied
- -25° to 40° ambient operating temperature

Product Specification:

Installation Type	Surface Mount
Input Voltage	220 - 240V
Luminaire Materials	Polycarbonate, Steel
Lifetime	40000
CRI	80
IK Rating	IK10
IP Rating	IP66
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.