




SKU	Base	Watts	lm/W	Lumens	Colour	Beam
<b>Dimmable CRI80</b>						
EN-DGU005-27	GU10	5W	106	530lm	2700K	60°
EN-DGU005-30	GU10	5W	112	560lm	3000K	60°
EN-DGU005-40	GU10	5W	120	600lm	4000K	60°
EN-DGU005-64	GU10	5W	120	600lm	6400K	60°
<b>Dimmable CRI90</b>						
EN-DGU005H-27	GU10	5W	86	400lm	2700K	60°
EN-DGU005H-30	GU10	5W	85	423lm	3000K	60°
EN-DGU005H-40	GU10	5W	98	491lm	4000K	60°
<b>Non-Dimmable CRI80</b>						
EN-GU005-27	GU10	5W	106	530lm	2700K	60°
EN-GU005-30	GU10	5W	112	560lm	3000K	60°
EN-GU005-40	GU10	5W	120	600lm	4000K	60°
EN-GU005-64	GU10	5W	120	600lm	6400K	60°


## Line Drawing



**EN-GU005**      **EN-DGU005H**  
(OD) 50mm Overall (Ø) (OD) 50mm Overall (Ø)  
(L) 57mm Length    (L) 57mm Length

**EN-DGU005**  
(OD) 50mm Overall (Ø)  
(L) 57mm Length

## Polar Curves



## Product Features:

- Featuring ThermoTec™ heat management technology
- Delivering up to 120lm/W
- Suitable for use in enclosed luminaires
- Sparkling low glare multifaceted lens
- 60° beam angle
- EN-DGU005 & EN-GU005 - CRI80
- EN-DGU005H - CRI90

## Product Specification:

Input Voltage	220 - 240V
Luminaire Materials	Aluminium Thermo Plastic
Lifetime L70	45000
CRI	80 or 90
IK Rating	IK06
IP Rating	IP20
Warranty	5 Years

## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.