



Colour options:




Black White

SKU	Watts	lm/W	Lumens	Colour	Beam
EN-LN1230-40*	30W	100	3000lm	4000K	120°
EN-LN1540-40*	40W	100	4000lm	4000K	120°

*Add suffix **W** or **BLK** for White or Black finish


Line Drawing



EN-LN1230	EN-LN1540
(L) 1200mm Length	(L) 1500mm Length
(W) 50mm Width	(W) 50mm Width
(H) 82mm Height	(H) 82mm Height

Polar Curves

40W 4000K 120°



Product Features:

- High quality extruded aluminium chassis
- Delivering 100lm/W
- Opal polycarbonate diffuser with uniform distribution
- Supplied with 2 metre suspension cable & surface mount brackets
- Suitable for surface mounting or suspension

Product Specification:

Installation Type	Suspended or Surface Mount
Input Voltage	220 - 240V
Luminaire Materials	Die Cast Aluminium, Polycarbonate
Lifetime	50000
CRI	80
IK Rating	IK08
IP Rating	IP20
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.