



**WATTAGE
SELECTABLE**

**COLOUR
SELECTABLE**

Colour :




White

Sku	Watts	lm/W	Lumens	Colour	Beam
EN-CWS1	10W	94	940lm	3000K	120°
		96	960lm	4000K	120°
		99	990lm	5700K	120°
	13W	92	1190lm	3000K	120°
		92	1200lm	4000K	120°
		97	1260lm	5700K	120°
	16W	84	1350lm	3000K	120°
		85	1360lm	4000K	120°
		90	1450lm	5700K	120°

Triac, Dali, 1-10V dimmable & EM options available, contact sales office for more information

Line Drawing




EN-CWS1


(H) 16mm Height
(OD) 235mm Overall (Ø)
(CO) 65mm -205mm Cutout (Ø)

Polar Curves

13W 4000K 120°



16W 4000K 120°



Product Features:

- Colour temperature can be switched between 3000K, 4000K and 5700K
- Wattage selectable between 10W, 13W and 16W
- Delivering up to 99lm/W
- Select colour temperature and wattage prior to installation
- Adjustable cutout between 65mm and 205mm
- 120° beam angle
- Supplied with integrated non-dimmable driver
- Can be surface mounted

Product Specification:

Installation Type	Recessed Surface
Input Voltage	220 - 240V
Luminaire Materials	Die Cast Aluminium, Polycarbonate
Lifetime	50000
CRI	80
IK Rating	IK06
IP Rating	IP20
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.