



Colour :




White


SKU	Watts	lm/W	Lumens	Colour	Beam
EN-PLPC06-40	6W	83	500lm	4000K	120°
EN-PLPC09-40	9W	94	850lm	4000K	120°
EN-PLPC12-40	12W	100	1200lm	4000K	120°
EN-PLPC18-40	18W	103	1850lm	4000K	120°

Triac, Dali, 1-10V dimmable & EM options available, contact sales office for more information

Line Drawing



Polar Curves



EN-PLPC06

(H) 21mm Height
(OD) 128mm Overall (Ø)
(CO) 115mm Cutout (Ø)

EN-PLPC12

(H) 21mm Height
(OD) 170mm Overall (Ø)
(CO) 150mm Cutout (Ø)

EN-PLPC09

(H) 21mm Height
(OD) 146mm Overall (Ø)
(CO) 130mm Cutout (Ø)

EN-PLPC18

(H) 21mm Height
(OD) 229mm Overall (Ø)
(CO) 210mm Cutout (Ø)

Product Features:

- Edge-lit low profile ideal for installations in limited recess space (21mm for downlight, 40mm space for driver)
- Delivering up to 103lm/W
- 120° beam angle
- Opal polycarbonate diffuser for even light distribution
- Supplied with remote non-dimmable constant current driver

Product Specification:

Installation Type	Recessed
Input Voltage	220 - 240V
Luminaire Materials	Aluminium, Polycarbonate
Lifetime	15000
CRI	80
IK Rating	IK06
IP Rating	IP40
Warranty	2 Years

Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.