



Colour options:




Black White

Sku	Watts	lm/W	Lumens	Colour	Beam
AA-DLR312-40*	12W	120	1440lm	4000K	90°
AA-DLR420-40*	20W	120	2400lm	4000K	90°
AA-DLR630-40*	30W	120	3600lm	4000K	90°
AA-DLR840-40*	40W	120	4800lm	4000K	90°

*Add suffix **W** or **BLK** for White or Black finish

Triac, Dali, 1-10V dimmable & EM options available, contact sales office for more information

Line Drawing



AA-DLR312

(H) 42mm Height
(OD) 108mm Overall (Ø)
(CO) 90mm Cutout (Ø)

AA-DLR420

(H) 63mm Height
(OD) 140mm Overall (Ø)
(CO) 115-125mm Cutout (Ø)

AP-DLR630


(H) 70mm Height
(OD) 190mm Overall (Ø)
(CO) 155-175mm Cutout (Ø)

AA-DLR840


(H) 77mm Height
(OD) 230mm Overall (Ø)
(CO) 200-210mm Cutout (Ø)

Polar Curves

30W 4000K 90°



40W 4000K 90°



Product Features:

- High powered COB with a multi faceted aluminium reflector
- 90° beam angle for maximum light distribution
- Downlight for commercial applications
- Dimmable available on request
- Delivering 120lm/W

Product Specification:

Installation Type	Recessed
Input Voltage	200 - 240V
Luminaire Materials	Die Cast Aluminium
Lifetime	50000
CRI	80+
IK Rating	IK03
IP Rating	IP20 Front (IP44 Back)
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.