




Colour options:



Sku	Watts	lm/W	Lumens	Colour	Beam
Non-Dimmable					
EN-DL10-30	10W	105	1050lm	3000K	100°
EN-DL10-40	10W	115	1150lm	4000K	100°
EN-DL15-30	15W	107	1600lm	3000K	100°
EN-DL15-40	15W	113	1700lm	4000K	100°
EN-DL23-30	23W	108	2500lm	3000K	100°
EN-DL23-40	23W	117	2700lm	4000K	100°
EN-DL30-30	30W	106	3200lm	3000K	100°
EN-DL30-40	30W	115	3450lm	4000K	100°
Triac Dimmable					
EN-DDL10-30	10W	90	900lm	3000K	100°
EN-DDL10-40	10W	96	960lm	4000K	100°
EN-DDL15-40	15W	96	1450lm	4000K	100°
EN-DDL20-40	20W	105	2100lm	4000K	100°
EN-DDL25-40	25W	102	2550lm	4000K	100°


Black option available as a special order, contact sales office for more information

Line Drawing



Polar Curves

30W 4000K 100°



EN-DL10

(H) 60mm Height
(OD) 120mm Overall (Ø)
(CO) 90mm Cutout (Ø)

EN-DL15

(H) 60mm Height
(OD) 150mm Overall (Ø)
(CO) 120mm Cutout (Ø)

EN-DL23

(H) 65mm Height
(OD) 200mm Overall (Ø)
(CO) 170mm Cutout (Ø)

EN-DL30

(H) 65mm Height
(OD) 235mm Overall (Ø)
(CO) 200mm Cutout (Ø)

EN-DDL10

(H) 60mm Height
(OD) 120mm Overall (Ø)
(CO) 90mm Cutout (Ø)

EN-DDL15

(H) 60mm Height
(OD) 150mm Overall (Ø)
(CO) 120mm Cutout (Ø)

EN-DDL20

(H) 65mm Height
(OD) 235mm Overall (Ø)
(CO) 200mm Cutout (Ø)

Product Features:

- ThermoTec™ heat management technology
- Delivering up to 117lm/W
- Pre-wired with 500mm 2 core cable
- Opal polycarbonate diffuser for even light distribution
- Supplied with integrated driver

Product Specification:

Installation Type	Recessed
Input Voltage	220 - 240V
Luminaire Materials	Polycarbonate
Lifetime	25000
CRI	80
IK Rating	IK03
IP Rating	IP44
Warranty	3 Years

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.