



Bezel Colour
Option:



Black

Sku	Watts	lm/W	Lumens	Colour	Beam
EN-BH108-40	8W	106	850lm	4000K	120°
EN-BH115-40	15W	103	1550lm	4000K	120°
EN-BH120-40	20W	103	2050lm	4000K	120°


Standard colour is white

Accessories

EN-BZ115BLK Utilite[™] 167mm Bezel Accessory for EN-BH115

EN-BZ120BLK Utilite[™] 221mm Bezel Accessory for EN-BH120


Line Drawing



EN-BH108 (OD) 167mm Overall Ø (P) 62mm Projection
EN-BH120 (OD) 221mm Overall Ø (P) 72mm Projection
EN-BH115 (OD) 167mm Overall Ø (P) 62mm Projection

Polar Curves

15W 4000K 120°



Product Features:

- Polycarbonate body and diffuser
- Delivering up to 106lm/W
- Pre-wired with 200mm cable
- Integrated driver for slim profile
- Interchangeable bezels (bezels do not sit flush to the wall)
- IK Rated IK06

Product Specification:

Installation Type	Surface
Input Voltage	220 - 240V
Luminaire Materials	Polycarbonate
Lifetime	25000
CRI	80
IK Rating	IK06
IP Rating	IP65
Warranty	3 Years

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.