



Colour options:




White



Black/Gold

Cat. No.	Watts	Colour	Lumens	Beam	Finish
AA-PD32018-30W	18W	3000K	1000	120°	White with white reflector
AA-PD32018-30BG	18W	3000K	1000	120°	Black with gold reflector
AA-PD40025-30W	25W	3000K	1500	120°	White with white reflector
AA-PD40025-3BG	25W	3000K	1500	120°	Black with gold reflector

Line Drawing



AA-PD32018


(OD) 320mm Overall (Ø)
(D) 64mm Depth

AA-PD40025

(OD) 400mm Overall (Ø)
(D) 64mm Depth

Polar Curves

25W 3000K 120°



600 Lumens



Product Features:

- Surface mounted
- Internal driver
- Flicker free
- Polycarbonate construction

Product Specification:

Installation Type	Surface Mount
Input Voltage	200 - 240V
Luminaire Materials	Polycarbonate
Lifetime	35,000
CRI	80
IK Rating	IK06
IP Rating	IP54
Warranty	3 Years

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.